

# Automatic Generation of Oracles for Exceptional Behaviors



**Alberto Goffi – [alberto.goffi@usi.ch](mailto:alberto.goffi@usi.ch)**

USI Università della Svizzera italiana (Lugano, Switzerland)

**Alessandra Gorla**

IMDEA Software Institute (Madrid, Spain)

**Michael D. Ernst**

University of Washington (Seattle, Washington, USA)

**Mauro Pezzè**

USI Università della Svizzera italiana (Lugano, Switzerland)

# The Oracle Problem

Automatically generated test cases **need oracles**

# The Oracle Problem

Automatically generated test cases **need oracles**

Developers **do not write** formal **specifications**

# The Oracle Problem

Automatically generated test cases **need oracles**

Developers **do not write** formal **specifications**

Developers **do write Javadoc** comments

# The Oracle Problem

Automatically generated test cases **need oracles**


Developers **do not write** formal **specifications**

Developers **do write Javadoc** comments




Automatically generate **oracles**  
**from Javadoc comments**


# Testers under-test exceptions




# Testers under-test exceptions



# Testers under-test exceptions



# Testers under-test exceptions



...and automatic testing does *not* help

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
    public Object next() {...}  
    ...  
}
```

...and automatic testing does *not* help

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
    public Object next() {...}  
    ...  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```

# What does an exception mean?

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
    public Object next() {...}  
    ...  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



**NullPointerException**

# What does an exception mean?

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
    public Object next() {...}  
    ...  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



**NullPointerException**

- 1. Expected behavior
- 2. Illegal input
- 3. Implementation bug



# What does an exception mean?

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
  
    /**  
     * @throws NullPointerException if either  
     *   the iterator or predicate are null  
     */  
    public Object next() {...}  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



**NullPointerException**

- 1. Expected behavior
- 2. Illegal input
- 3. Implementation bug



# What does an exception mean?

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
  
    /**  
     * @throws NullPointerException if either  
     *   the iterator or predicate are null  
     */  
    public Object next() {...}  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



**NullPointerException**

1. **Expected behavior**
2. Illegal input
3. Implementation bug

# What does an exception mean?

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
  
    /**  
     * @throws NullPointerException if either  
     *   the iterator or predicate are null  
     */  
    public Object next() {...}  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



**NullPointerException**



1. Expected behavior

2. Illegal input
3. Implementation bug

# Consider another implementation

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
  
    /**  
     * @throws NullPointerException if either  
     *   the iterator or predicate are null  
     */  
    public Object next() {...}  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



No Exceptions

- 1. Expected behavior
- 2. Illegal input
- 3. Implementation bug



# Consider another implementation

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
  
    /**  
     * @throws NullPointerException if either  
     * the iterator or predicate are null  
     */  
    public Object next() {...}  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



No Exceptions

1. Expected behavior
2. Illegal input
3. Implementation bug

# Consider another implementation

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
  
    /**  
     * @throws NullPointerException if either  
     * the iterator or predicate are null  
     */  
    public Object next() {...}  
}
```

```
public void test {  
    FilterIterator i = new FilterIterator(null, null);  
    i.next();  
}
```



**No Exceptions**

*MisSED ALARM*

1. Expected behavior
2. Illegal input
3. Implementation bug

Test

```
public void test {  
    FilterIterator i =  
        new FilterIterator(null, null);  
    i.next();  
}
```

# Test Documentation

```
public void test {
    FilterIterator i =
        new FilterIterator(null, null);
    i.next();
}
```

```
/***
 * @throws NullPointerException if either
 *   the iterator or predicate are null
 */
public Object next() {...}
```

Test

+

Documentation


```
public void test {  
    FilterIterator i =  
        new FilterIterator(null, null);  
    i.next();  
}
```

```
/**  
 * @throws NullPointerException if either  
 *   the iterator or predicate are null  
 */  
public Object next() {...}
```

Test



Documentation



Test + Oracle

```
public void test {
    FilterIterator i =
        new FilterIterator(null, null);
    i.next();
}
```

```
/** 
 * @throws NullPointerException if either
 *   the iterator or predicate are null
 */
public Object next() {...}
```




```
public void test {
    FilterIterator i =
        new FilterIterator(null, null);
    if (i.getIterator() == null ||
        i.getPredicate() == null) {
        try {
            i.next();
            fail("Expected NPE not thrown");
        } catch(NullPointerException e) {
            // Expected exception
        }
    } else {
        i.next();
    }
}
```

Test



Documentation



Test + Oracle

```
public void test {  
    FilterIterator i =  
        new FilterIterator(null, null);  
    i.next();  
}
```

```
/**  
 * @throws NullPointerException if either  
 *   the iterator or predicate are null  
 */  
public Object next() {...}
```




```
public void test {  
    FilterIterator i =  
        new FilterIterator(null, null);  
    if (i.getIterator() == null ||  
        i.getPredicate() == null) {  
        try {  
            i.next();  
            fail("Expected NPE not thrown");  
        } catch(NullPointerException e) {  
            // Expected exception  
        }  
    } else {  
        i.next();  
    }  
}
```

Test



Documentation




Test + Oracle


```
public void test {
    FilterIterator i =
        new FilterIterator(null, null);
    i.next();
}
```



```
/** @throws NullPointerException if either
 * the iterator or predicate are null
 */
public Object next() {...}
```





```
public void test {
    FilterIterator i =
        new FilterIterator(null, null);
    if (i.getIterator() == null ||
        i.getPredicate() == null) {
        try {
            i.next();
            fail("Expected NPE not thrown");
        } catch(NullPointerException e) {
            // Expected exception
        }
    } else {
        i.next();
    }
}
```








1. Method Signature
2. Expected Exceptions
3. Conditions (Text)




1. Method Signature
2. Expected Exceptions
3. Conditions (Text)


```
/**  
 * @throws NullPointerException  
 *   if either the iterator  
 *   or predicate are null  
 */  
public Object next() {...}
```




1. FilterIterator.next()
2. NullPointerException
3. "if either the iterator or predicate are null"




1. Method Signature
2. Expected Exceptions
3. Conditions (Text)



1. Method Signature
2. Expected Exceptions
3. **Conditions (Code)**




1. Method Signature
2. Expected Exceptions
3. Conditions (Text)




1. Method Signature
2. Expected Exceptions
3. **Conditions (Code)**


1. `FilterIterator.next()`
2. `NullPointerException`
3. "if either the iterator or predicate are null"



1. `FilterIterator.next()`
2. `NullPointerException`
3. `getIterator() == null || getPredicate() == null`



1. `FilterIterator.next()`
2. `NullPointerException`
3. `getIterator() == null ||`  
`getPredicate() == null`



Test  
+

```
public void test {
    FilterIterator i = new FilterIterator(null, null);
    i.next();
}
```


1. `FilterIterator.next()`  
 2. `NullPointerException`  
 3. `getIterator() == null || getPredicate() == null`

—

Test + Oracle


```
public void test {
    FilterIterator i = new FilterIterator(null, null);
    if (i.getIterator()==null || i.getPredicate()==null) {
        try {
            i.next();
            fail("Expected NPE not thrown");
        } catch(NullPointerException e) {
            // Expected exception
        }
    } else { i.next(); }
}
```

# Natural Language Condition




Java boolean condition


“if the array is empty”





**"if foo is positive"**



# Natural Language Condition



## Condition Translator



# Java Condition



"if either the iterator or predicate are null"



"if either the iterator or predicate are null"

Proposition

Subject

Predicate

---

1

"iterator"

"are null"



"if either the **iterator** or **predicate** are null"

Proposition	Subject	Predicate
1	"iterator"	"are null"
2	"predicate"	"are null"





"if either the **iterator** or **predicate** are null"



"if either the iterator or predicate are null"

Proposition	Subject	Predicate
1	"iterator"	"are null"
2	"predicate"	"are null"






Proposition	Subject	Predicate
1	"iterator"	"are null"
2	"predicate"	"are null"



**Subject: “iterator”**



**Subject: “iterator”**


## Candidates

Formal Parameters

Class Name

Non-void Nullary Methods

Fields



Subject: “iterator”


## Candidates

Formal Parameters

Class Name

Non-void Nullary Methods

Fields



Candidate

**FilterIterator**


**getIterator**

**getPredicate**

**next**

...

```
public class FilterIterator implements Iterator {  
    public FilterIterator(Iterator i, Predicate p) {...}  
    public Iterator getIterator() {...}  
    public Predicate getPredicate() {...}  
    public Object next() {...}  
    ...  
}
```



Subject: “iterator”


## Candidates

Formal Parameters


Class Name

Non-void Nullary Methods

Fields




Candidate	Distance
FilterIterator	6
getIterator	3
getPredicate	9
next	6
...	




Subject: “iterator” => **getIterator()**

## Candidates

Formal Parameters  
Class Name  
Non-void Nullary Methods  
Fields




Candidate	Distance
FilterIterator	6
<b>getIterator</b>	<b>3</b>
getPredicate	9
next	6
...	



Proposition	Subject	Predicate
-------------	---------	-----------

1	"iterator"	"are null"
---	------------	------------

2	"predicate"	"are null"
---	-------------	------------



Proposition	Subject	Predicate
-------------	---------	-----------

1	FilterIterator.getIterator()	"are null"
---	------------------------------	------------


2	FilterIterator.getPredicate()	"are null"
---	-------------------------------	------------



Proposition	Subject	Predicate
1	<code>FilterIterator.getIterator()</code>	"are null"
2	<code>FilterIterator.getPredicate()</code>	"are null"



Proposition	Subject	Predicate
1	<code>FilterIterator.getIterator()</code>	"are null"
2	<code>FilterIterator.getPredicate()</code>	"are null"



Proposition	Subject	Predicate
1	<code>FilterIterator.getIterator()</code>	"==null"
2	<code>FilterIterator.getPredicate()</code>	"==null"



```
/**  
 * @throws IllegalArgumentException if employees is empty  
 */  
public void sortByAge(List employees) {...}
```

Proposition	Subject	Predicate
1	employees	"is empty"



```

/**
 * @throws IllegalArgumentException if employees is empty
 */
public void sortByAge(List employees) {...}

```

Proposition	Subject	Predicate
1	employees	“is empty”
Candidate		Distance
clear		7
<b>isEmpty</b>		<b>1</b>
iterator		6
size		7
...		



```
/**  
 * @throws IllegalArgumentException if employees is empty  
 */  
public void sortByAge(List employees) {...}
```

Proposition	Subject	Predicate
1	employees	“is empty”
Condition		Translation
1		employees.isEmpty()



"if either the iterator or predicate are null"

Condition	Translation
1	<code>FilterIterator.getIterator() == null</code>
2	<code>FilterIterator.getPredicate() == null</code>

# Positive conditions

“if either the iterator or predicate **are** null”

Condition	Translation
1	<code>(FilterIterator.getIterator() == null) == true</code>
2	<code>(FilterIterator.getPredicate() == null) == true</code>

# Positive conditions

"if either the iterator or predicate **are** null"

Condition	Translation
1	<code>(FilterIterator.getIterator() == null) == true</code>
2	<code>(FilterIterator.getPredicate() == null) == true</code>


# Negative conditions

"if either the iterator or predicate **aren't** null"


Condition	Translation
1	<code>(FilterIterator.getIterator() == null) == false</code>
2	<code>(FilterIterator.getPredicate() == null) == false</code>

# Evaluation


# From NL to Java Conditions




# From NL to Java Conditions




# From NL to Java Conditions




# False Alarms – Google Guava




# False Alarms – Google Guava




# True Alarms – Apache Commons




# True Alarms – Apache Commons




# True Alarms – Apache Commons




# True Alarms – Apache Commons



# True Alarms – Apache Commons



# True Alarms – Apache Commons



# What's next?

## **Oracles for exceptions on arrays/containers elements**

`@throws IllegalArgumentException` if the array contains null

# What's next?

## Oracles for exceptions on arrays/containers elements

*@throws IllegalArgumentException* if the array contains null

### input values

*@param* foo must not be null


```
void sort(@NotNull int[] a)
```

### return values



*@return* the size of the array

...more


# Testers under-test exceptions




# Testers under-test exceptions




# Testers under-test exceptions





Toradocu




## From NL to Java Conditions




# Testers under-test exceptions




## From NL to Java Conditions




## False Alarms – Google Guava




# Testers under-test exceptions




-25%



[github.com/albertogoffi/toradocu](https://github.com/albertogoffi/toradocu)  
alberto.goffi@usi.ch



**Precision: 92%**  
**Recall: 73%**



(EvoSuite Test Cases)



# Related Work

## Heuristics

JCrasher, Crash'n'Check (Csallner, and Smaragdakis. ICSE '05)

Randoop (Pacheco, Lahiri, Ernst, and Ball. ICSE '07)

## Specifications

ASTOOT (Doong, and Frankl. TOSEM '94)

Models, contracts, ...

## Properties

Cross-checking oracles (Carzaniga, Goffi, Gorla, Mattavelli, and Pezzè. ICSE '14)

Metamorphic testing (Chen, Kuo, Tse, and Zhou. STEP '13)

Symmetric testing (Gotlieb. ISSRE '03)

## Natural Language Documentation

**@tComment** (Tan, Marinov, Tan, and Leavens. ICST '12)

aComment (Tan, Zhou, and Padioleau. ICSE '11)

iComment (Tan, Yuan, Krishna, and Zhou. SOSP '07)

# When does Toradocu fail?

## Conditions on the elements in a container

- if collection or any of its elements is null
- if any element in the arrays is null
- if notes has fewer than 2 elements

## Specific checks

- if the runtime type of the specified array is not a supertype of the runtime type of every element in this collection
- if  $x > 0$

## Missing predicate translation (No output)

- if the charset is not valid
- if closed

# Examples

```
@throws NullPointerException if the predicate or
either closure is null
... ifClosure(Predicate predicate, Closure
trueClosure, Closure falseClosure) {...}
==> predicate == null || trueClosure == null ||
falseClosure == null
```

```
@throws UnsupportedOperationException if the
comparator is locked
... checkLocked() {...}
==> target.isLocked()
```